

Chains & sprockets	Wear strips	Side guide brackets & accessories	Levelers
Modular belts & sprockets	Chain & belt return systems	Frame & structure supports	Bearings
Curves & tracks	Side guide solutions	Miscellaneous products	Related information




Click here for related information.

50520a


www.SystemPlastSmartGuide.com

Wear strips




Material:
Extruded ultra high molecular weight polyethylene.
Max. continuous service temperature in air 90° C.
Water absorption coefficient = 0.

MOQ Min. order quantity: 300 m



See other wear strips:

50530a



	UHMW-PE Green	UHMW-PE Black	Nolu®-S			
	Item description	Item description	Item description			
	VG-L20M-G-200	VG-L20M-B-200	VG-L20M-NS-200	60 m	-	60 m
	VG-Z18M-G-200	VG-Z18M-B-200	VG-Z18M-NS-200	60 m	-	60 m
	VG-Z20M-G-200	VG-Z20M-B-200	VG-Z20M-NS-200	60 m	-	60 m
	VG-Z20WM-G-200	VG-Z20WM-B-200	VG-Z20WM-NS-200	60 m	-	60 m
	VG-J21M-G-200	VG-J21M-B-200	VG-J21M-NS-200	60 m	-	60 m
Notes: applicable from 2.5 to 4 mm thick sheet metal.						
	VG-JL19M-G-200	VG-JL19M-B-200	VG-JL19M-NS-200	60 m	-	60 m
Notes: applicable from 2.5 to 4 mm thick sheet metal.						
	VG-J23M-G-20	VG-J23M-B-20	VG-J23M-NS-20	-	6 m	60 m