

BALDOR® • RELIANCE

Product Information Packet

VM7034T

1.5//1HP,1755//1460RPM,3PH,60//50HZ,145T

Part Detail							
Revision:	F	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3521M	Elec. Spec:	35WGZ541	CD Diagram:	CD0005
Enclosure:	XPFC	Mfg Plant:		Mech. Spec:	35E380	Layout:	35LYE380
Frame:	145TC	Mounting:	F1	Poles:	04	Created Date:	06-02-2010
Base:	N	Rotation:	R	Insulation:	B	Eff. Date:	10-08-2013
Leads:	9#18					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP1426XPSL					
NO.		CC	010A		
SER.					
SPEC.	35E380Z541H1				
CAT.NO.	VM7034T				
HP	1.5//1	T. CODE	T3C		
VOLTS	230/460//190/380				
AMPS	4.8/2.4//4.2/2.1				
RPM	1755//1460				
HZ	60//50	PH	3	CL	B
SER.F.	1.00	DES	B	CODE	M
RATING	40C AMB-CONT				
FRAME	145TC	NEMA-NOM-EFF	84		
USABLE AT 208V		PF	70		
BLANK					

Parts List		
Part Number	Description	Quantity
SA197612	SA 35E380Z541H1	1.000 EA
RA184997	RA 35E380Z541H1	1.000 EA
35CB3001A02SP	EXPL PROOF CONDUIT BOX, 3/4"PIPE TAP LEA	1.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
HW3001B01	003SS CUP WASHER, FOR #8 SCREW	1.000 EA
35EP3700A01SP	FR ENDPLATE, XPFC	1.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
35EP3702A01SP	PU EP-205 BRG-35X-56C-143-5TC	1.000 EA
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 EA
HA3013A01	1/2-20X5/8 SPL.HX BOLT	2.000 EA
HW3021C06	3/32 DI X .625 PIN (F/S)	2.000 EA
XY3118A12	5/16-18 HEX NUT DIRECTIONAL SERRATION	4.000 EA
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 EA
35FH4005A01SP	IEC FH NO GREASER W/AUTOPHORETIC PRIMER	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
35CB3500A01SP	CONDUIT BOX LID, MACH	1.000 EA
51XN2520A16	SCREW, HEX WS SLT, ZN, 1/4-20 X 1.00	4.000 EA
HW2501D13SP	KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A01	KEY RETAINER 7/8" DIA SHAFT	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	6.000 EA
NP0018	NP- XP CONDUIT BOX DO NOT MAKE SELLABLE	1.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB
35FN3002A05SP	EXFN, PLASTIC, 6.376 OD, .638 ID	1.000 EA
MG1025G29	MUNSELL 4.5Y 5.3/0.7 DARK CHARCOAL GREY	0.017 GA

Parts List (continued)		
Part Number	Description	Quantity
MG1025Z20	ACTIVATOR WILKOFAS 060.32	0.010 GA
HA3104A08	THRUBOLT-5/16-18X9.375 X X	4.000 EA
LB1119N	WARNING LABEL	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0145B01	CONNECTION LABEL	1.000 EA
NP1426XPSL	SS XP UL CSA CC CL-I GP-D CL-II GP-F&G	1.000 EA
36PA1000	PACK GROUP W/LB5001	1.000 EA
PK3082	STYROFOAM CRADLE	1.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1200/bx) 10/13	1.000 EA

AC Induction Motor Performance Data

Record # 28529 - Typical performance - not guaranteed values


Winding: 35WGZ541-R004	Type: 3521M	Enclosure: XPFC
-------------------------------	--------------------	------------------------

Nameplate Data				460 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	1.5//1			Full Load Torque	4.43 LB-FT
Volts	230/460//190/380			Start Configuration	direct on line
Full Load Amps	4.8/2.4//4.2/2.1			Breakdown Torque	19.4 LB-FT
R.P.M.	1755//1460			Pull-up Torque	10.5 LB-FT
Hz	60//50	Phase	3	Locked-rotor Torque	13.8 LB-FT
NEMA Design Code	B	KVA Code	M	Starting Current	19 A
Service Factor (S.F.)	1			No-load Current	1.59 A
NEMA Nom. Eff.	84	Power Factor	70	Line-line Res. @ 25°C	10.1 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	56°C
				Rotor inertia	0.124 LF ²

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	30	48	62	70	77	80
Efficiency	68.2	79.4	83	84	83.9	83
Speed	1792	1782	1772	1761	1749	1735
Line amperes	1.64	1.8	2.04	2.35	2.71	3.12

Performance Graph at 460V, 60Hz, 1.5HP Typical performance - Not guaranteed values



12/18/2014 ACPERF, record # 28529

