

## Straight Globe Valves

18-217

**Features:**

- ideal for wet and combination systems
- used with a fire hose rack assembly, or as a fire department outlet connection
- aluminum handwheel
- maximum operating pressure: **300 PSI** at 70°F (21°C)

**Female x Male**

Inlet Female	Outlet Male	Cast Brass Part #	Price/E	Wt. Lbs.
1½" NPT	1½" NST (NH)	<b>SGV150F</b>	<b>\$374.05</b>	6.0
1½" CT	1½" CT	<b>SGV150__</b> <sup>1</sup>	<b>POR</b>	6.0
2½" NPT	2½" NST (NH)	<b>SGV250F</b>	<b>547.60</b>	9.6
2½" CT	2½" CT	<b>SGV250__</b> <sup>1</sup>	<b>POR</b>	9.6

<sup>1</sup> Customer Thread (*must specify*) refer to legend on page 566




**Female x Female**

Inlet Female NPT	Outlet Female NPT	Cast Brass Part #	Price/E	Wt. Lbs.
1½"	1½"	<b>SGVF150</b>	<b>\$374.05</b>	6.0
2½"	2½"	<b>SGVF250</b>	<b>547.60</b>	8.0

**Dimensions**

Size	A	B	C (closed)	D (open)	Wt. Lbs.
1½"	2-3/8"	4-3/4"	7-1/4"	8"	5.0
2½"	3-9/32"	6-9/16"	7-3/8"	8-1/8"	9.3



## Wharf Hydrants

18-251

**Features:**

- used to provide a fire department outlet connection
- pentagon nut at top of spindle discourages unauthorized use
- hydrostatically tested
- maximum operating pressure: **300 PSI** at 70°F (21°C)

Inlet Female NPT	Outlet Male NST (NH)	Height Open	Height Closed	Cast Brass Part #	Price/E	Wt. Lbs.
3"	2½"	16.38	14.25	<b>WHYD3025F</b>	<b>\$932.15</b>	31
4"	2½"	16.38	14.25	<b>WHYD4025F</b>	<b>1053.70</b>	23
4"	4½"	18.13	15.63	<b>WHYD4045F</b>	<b>1310.00</b>	41

**Replacement Parts**

Description	Part #	Price/E
hand wheel	<b>46-030-00025</b>	<b>\$21.25</b>
pentagon hex nut	<b>44-251-00006</b>	<b>15.15</b>



P